



Dimension board

| | |
|----------------------------|---------|
| LENGTH | 2200 mm |
| WIDTH | 190 mm |
| TOTAL THICKNESS | 15.0 mm |
| THICKNESS TOP LAYER | 4 mm |

Dimension pack

| | |
|---------------------------|---------------------|
| PACK LENGTH | 2210 mm |
| PACK WIDTH | 200 mm |
| PACK THICKNESS | 130 mm |
| PACK WEIGHT | 30 kg |
| LAYERS/BOX | 8 |
| M²/PACK | 3.34 m ² |

Dimension pallet

| | |
|-----------------------------|-----------------------|
| PALLET LENGTH | 2230 mm |
| PALLET WIDTH | 1000 mm |
| PALLET HEIGHT | 1030 mm |
| PALLET WEIGHT | 1050 kg |
| PACKS/PALLET | 35 |
| M²/PALLET | 116.90 m ² |

CHARACTERISTICS

Top layer

| | |
|----------------------------|-------------------------|
| WOOD SPECIES | Bamboo |
| LATIN NAME | Phyllostachys Pubescens |
| GRADE | CARB |
| CONSTRUCTION | 3-layer |
| THICKNESS TOP LAYER | 4 mm |
| PATTERN | 1 strip |
| CUTTING METHOD | Zaagfineer |
| BEVEL | No |
| FINISH | Oil |
| SURFACE STRUCTURE | Smooth |

Composition of the support

| | |
|--------------------------------|-------------|
| SUPPORT TYPE | Populier |
| WOOD SPECIES SUPPORT | Populier |
| TOTAL THICKNESS SUPPORT | 11 mm |
| ADHESION | Kruiselings |

Installation

| | | |
|-------------------|--|---------------------------|
| SYSTEM | APPLICATIONS | UNDERFLOOR HEATING |
| Tongue and groove | Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use. | No |
| | | RE-SANDABLE |
| | | Yes |

TECHNICAL SPECIFICATIONS

| | Norm | Result |
|-----------------------|---------------------|------------------------|
| REACTION TO FIRE | EN 13501-1 | Dfl-S1 |
| FORMALDEHYDE EMISSION | EN 717-1 | E1 |
| PCP | CEN/TR 14823 | ≤ 5ppm |
| THERMAL CONDUCTIVITY | EN 12667 / ISO 8302 | 0,11m ² k/w |
| BIOLOGICAL DURABILITY | EN 335 | Class 1 |
| BREAKING STRENGTH | EN 1533 | Pass |
| SLIPPERINESS | EN 15676 | Pass |
| MOISTURE CONTENT | EN 13183-1 | 7% (+/-2%) |

CERTIFICATION



EN 14342

