



Dimension board

LENGTH	1900 mm
WIDTH	190 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	Min 7 Pl x 1900 mm

Dimension pack

PACK LENGTH	1910 mm
PACK WIDTH	200 mm
PACK THICKNESS	130 mm
PACK WEIGHT	26 kg
LAYERS/BOX	8
M²/PACK	2.89 m ²

Dimension pallet

PALLET LENGTH	1930 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	1160 mm
PALLET WEIGHT	1040 kg
PACKS/PALLET	40
M²/PALLET	115.60 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	4 mm
PATTERN	1 strip
CUTTING METHOD	Gekliefd
BEVEL	4 sides aged bevel
SURFACE STRUCTURE	Geklieft

Composition of the support

SUPPORT TYPE	Populier
WOOD SPECIES SUPPORT	Populier
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		No

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

