



Dimension board

LENGTH	540 mm
WIDTH	90 mm
TOTAL THICKNESS	20.0 mm
THICKNESS TOP LAYER	8 mm

Dimension pack

PACK LENGTH	550 mm
PACK WIDTH	100 mm
PACK THICKNESS	211 mm
PACK WEIGHT	6 kg
LAYERS/BOX	10
M²/PACK	0.49 m ²

Dimension pallet

PALLET LENGTH	570 mm
PALLET WIDTH	1050 mm
PALLET HEIGHT	1050 mm
PALLET WEIGHT	924 kg
PACKS/PALLET	154
M²/PALLET	75.46 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Olm
LATIN NAME	Ulmus
GRADE	OLDWOOD
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	8 mm
PATTERN	Hungarian point
CUTTING METHOD	Gekliefd
BEVEL	Micro bevel 4 sides
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	12 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	No RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

