



Dimension board

LENGTH	1900 mm
WIDTH	189 mm
TOTAL THICKNESS	10.0 mm
THICKNESS TOP LAYER	2 mm
LAYER CONTENTS	Min 7 Pl x 1900 mm

Dimension pack

PACK LENGTH	1910 mm
PACK WIDTH	200 mm
PACK THICKNESS	90 mm
PACK WEIGHT	17 kg
LAYERS/BOX	8
M²/PACK	2.87 m ²

Dimension pallet

PALLET LENGTH	1910 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	1200 mm
PALLET WEIGHT	1020 kg
PACKS/PALLET	60
M²/PALLET	172.20 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	HOME
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	2 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	2along0.50
FINISH	Lacquer
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	8 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

