



Dimension board

LENGTH	1260 mm
WIDTH	180 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	Min 7 Pl x 1260 mm

Dimension pack

PACK LENGTH	1260 mm
PACK WIDTH	185 mm
PACK THICKNESS	120 mm
PACK WEIGHT	17 kg
LAYERS/BOX	8
M²/PACK	1.81 m ²

Dimension pallet

PALLET LENGTH	1260 mm
PALLET WIDTH	950 mm
PALLET HEIGHT	1050 mm
PALLET WEIGHT	680 kg
PACKS/PALLET	40
M²/PALLET	72.40 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	4 mm
PATTERN	Square
CUTTING METHOD	Zaagfineer
BEVEL	4 sides aged bevel
SURFACE STRUCTURE	Antique

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

