



Dimension board

LENGTH	2200 mm
WIDTH	240 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	Min 4 Pl x 2200 mm

Dimension pack

PACK LENGTH	2210 mm
PACK WIDTH	250 mm
PACK THICKNESS	100 mm
PACK WEIGHT	28 kg
LAYERS/BOX	6
M²/PACK	3.17 m ²

Dimension pallet

PALLET LENGTH	2210 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	1120 mm
PALLET WEIGHT	1245 kg
PACKS/PALLET	45
M²/PALLET	142.65 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABC
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	4 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfinez
BEVEL	Bevel 2 long sides 0,75 mm
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Populier
WOOD SPECIES SUPPORT	Populier
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

