



Dimension board

LENGTH	600 mm
WIDTH	120 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	8Pl Links + 8Pl Rechts 600mm

Dimension pack

PACK LENGTH	620 mm
PACK WIDTH	250 mm
PACK THICKNESS	125 mm
PACK WEIGHT	13 kg
LAYERS/BOX	16
M²/PACK	1.15 m ²

Dimension pallet

PALLET LENGTH	640 mm
PALLET WIDTH	1040 mm
PALLET HEIGHT	870 mm
PALLET WEIGHT	832 kg
PACKS/PALLET	64
M²/PALLET	73.60 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABC
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	4 mm
PATTERN	Herringbone
CUTTING METHOD	Zaagfineer
BEVEL	Micro
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

