



Dimension board

LENGTH	520 mm
WIDTH	92 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	16

Dimension pack

PACK LENGTH	590 mm
PACK WIDTH	190 mm
PACK THICKNESS	125 mm
PACK WEIGHT	8 kg
LAYERS/BOX	16
M²/PACK	0.77 m ²

Dimension pallet

PALLET LENGTH	560 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	870 mm
PALLET WEIGHT	640 kg
PACKS/PALLET	80
M²/PALLET	61.60 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABC
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	4 mm
PATTERN	Hungarian point
CUTTING METHOD	Zaagfineer
BEVEL	4 langsijden microvelling
FINISH	Lacquer
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION

