



## Dimension board

|                            |                     |
|----------------------------|---------------------|
| <b>LENGTH</b>              | 1200 mm             |
| <b>WIDTH</b>               | 165 mm              |
| <b>TOTAL THICKNESS</b>     | 9.5 mm              |
| <b>THICKNESS TOP LAYER</b> | 1 mm                |
| <b>LAYER CONTENTS</b>      | Min 10 Pl x 1200 mm |

## Dimension pack

|                           |                     |
|---------------------------|---------------------|
| <b>PACK LENGTH</b>        | 1250 mm             |
| <b>PACK WIDTH</b>         | 175 mm              |
| <b>PACK THICKNESS</b>     | 125 mm              |
| <b>PACK WEIGHT</b>        | 21 kg               |
| <b>LAYERS/BOX</b>         | 13                  |
| <b>M<sup>2</sup>/PACK</b> | 2.57 m <sup>2</sup> |

## Dimension pallet

|                             |                       |
|-----------------------------|-----------------------|
| <b>PALLET LENGTH</b>        | 1250 mm               |
| <b>PALLET WIDTH</b>         | 1050 mm               |
| <b>PALLET HEIGHT</b>        | 1100 mm               |
| <b>PALLET WEIGHT</b>        | 1000 kg               |
| <b>PACKS/PALLET</b>         | 48                    |
| <b>M<sup>2</sup>/PALLET</b> | 123.36 m <sup>2</sup> |

## CHARACTERISTICS

## Top layer

|                            |                     |
|----------------------------|---------------------|
| <b>WOOD SPECIES</b>        | Oak                 |
| <b>LATIN NAME</b>          | Quercus Robur       |
| <b>GRADE</b>               | CLASSIC             |
| <b>CONSTRUCTION</b>        | 3-layer             |
| <b>THICKNESS TOP LAYER</b> | 1 mm                |
| <b>PATTERN</b>             | 1 strip             |
| <b>CUTTING METHOD</b>      | Zaagfineer          |
| <b>BEVEL</b>               | Micro bevel 4 sides |
| <b>FINISH</b>              | Lacquer             |
| <b>SURFACE STRUCTURE</b>   | Smooth              |

## Composition of the support

|                                |             |
|--------------------------------|-------------|
| <b>SUPPORT TYPE</b>            | HDF         |
| <b>WOOD SPECIES SUPPORT</b>    | Berk        |
| <b>TOTAL THICKNESS SUPPORT</b> | 8 mm        |
| <b>ADHESION</b>                | Kruiselings |

## Installation

|               |  |                           |
|---------------|--|---------------------------|
| <b>SYSTEM</b> | <b>APPLICATIONS</b>  | <b>UNDERFLOOR HEATING</b> |
| Click         | Light household use.<br>Moderate commercial use.<br>Normal commercial use.<br>Normal household use.<br>Intensive commercial use. | Yes                       |
|               |  | <b>RE-SANDABLE</b>        |
|               |  | No                        |

**TECHNICAL SPECIFICATIONS**

|                       | Norm                | Result                 |
|-----------------------|---------------------|------------------------|
| REACTION TO FIRE      | EN 13501-1          | Dfl-S1                 |
| FORMALDEHYDE EMISSION | EN 717-1            | E1                     |
| PCP                   | CEN/TR 14823        | ≤ 5ppm                 |
| THERMAL CONDUCTIVITY  | EN 12667 / ISO 8302 | 0,11m <sup>2</sup> k/w |
| BIOLOGICAL DURABILITY | EN 335              | Class 1                |
| BREAKING STRENGTH     | EN 1533             | Pass                   |
| SLIPPERINESS          | EN 15676            | Pass                   |
| MOISTURE CONTENT      | EN 13183-1          | 7% (+/-2%)             |

**CERTIFICATION**

