



Size

MIN LENGTH	50 mm
MAX LENGTH	240 mm
MIN. THICKNESS	3 mm
MAX. THICKNESS	20 mm
AVERAGE THICKNESS	10 mm

Size

ROW LENGTH	600 mm
LENGTH	600 mm
WIDTH	300 mm
MIN. THICKNESS	mm
MAX. THICKNESS	31 mm

Size **Pack**

PACK LENGTH	710 mm
PACK WIDTH	310 mm
PACK THICKNESS	140 mm
LAYERS/PACK	4
M²/PACK	0.72 m ²

Characteristics

WOOD SPECIES	Walnut
LATIN NAME	Juglans nigra L.
GRADE	ABCD
CONSTRUCTION	Samengesteld

TOTAL THICKNESS SUPPORT	11 mm
SURFACE STRUCTURE	Axe split
COLOUR FINISH	Axe split Unfinished

Installation

INSTALLATION	Nail down
DIRECTION	Horizontal Vertical

Certification

This product conforms to CE-standard EN 14951: Solid wood panelling and cladding

- Formaldehyde-emission, determined according to standard EN 13183-1:E1
- Moisture content, determined according to standard EN 13183-1: 10% (+/-2%). Suitable for use in dry rooms with a moisture content of 50% to 60%
- Width Shrinkage, complies with standard EN 13647
- Reaction to fire, determined according to standard EN 13501-1: D-s1, d0
- PCP (pentachloorfenol) < 5 ppm
- Density & thickness: 390, 9/5
- Water-vapour permeability: NPD
- Thermal conductivity: 0,04 W/mK
- Sound absorption: NPD
- Biological durability: Class 3

Technical specifications

Suitable for indoor use only.